

Lord Adhesives Metech 3542 Platinum Silver Conductor Composition

Category: Polymer, Adhesive

Material Notes:

These conductor compositions employ a state of the art mixed bond frit system to enhance adhesion and conductivity values while offering a range of cost effective conductors compatible with most resistor and dielectric systems. All information provided by Lord.

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lord-Adhesives-Metech-3542-Platinum-Silver-Conductor-Composition.php

Physical Properties	Metric	English	Comments
Brookfield Viscosity	180000 - 220000 cP	180000 - 220000 cP	HBT, Spindle #SC4-14 @ 10rpm
	@Temperature 25.0 °C	@Temperature 77.0 °F	
Thickness	12.0 - 14.0 microns	0.472 - 0.551 mil	Fired

Electrical Properties	Metric	English	Comments
Surface Resistivity per Square	0.011 ohm	0.011 ohm	

Processing Properties	Metric	English	Comments
Shelf Life	12.0 Month	12.0 Month	
	@Temperature 25.0 ðC	@Temperature 77.0 °F	

Descriptive Properties	Value	Comments
Adhesion	3-4	lbs; aged
	5-6	lbs; initial
Coverage (cm²/gm)	70- 75	Calculated from 50 micron wet film
Line Resolution (microns)	125	
Solder Leach Resistance (cycles)	5	Number of 5-second cycles required to leach 50% of a 10 mil wide conductive line using 62Sn/36Pb/2Ag at 230°C
Solder Wetting (seconds)	< 3	Time required to 100% solder wet 0.08" x 0.08" pad size using 62Sn/36Pb/2Ag at 230°C

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842



Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China