

## Loxim 430 01HB Nylon 6,6

Category : Polymer , Thermoplastic , Nylon , Nylon 66 , Nylon 66, 30% Glass Fiber Filled , Nylon 66, Glass Fiber Filled, Flame Retardant

**Material Notes:**

Information provided by Loxim Industries

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Loxim-430-01HB-Nylon-66.php](http://www.lookpolymers.com/polymer_Loxim-430-01HB-Nylon-66.php)

Physical Properties	Metric	English	Comments
Specific Gravity	1.34 g/cc	1.34 g/cc	ASTM D792
Linear Mold Shrinkage	0.0030 cm/cm	0.0030 in/in	ASTM D1299

Mechanical Properties	Metric	English	Comments
Tensile Strength at Break	180 MPa	26100 psi	ASTM D683
Elongation at Break	3.0 - 4.0 %	3.0 - 4.0 %	ASTM D638
Flexural Modulus	8.50 GPa	1230 ksi	ASTM D790
Izod Impact, Notched	1.10 J/cm	2.06 ft-lb/in	ASTM D256

Thermal Properties	Metric	English	Comments
Deflection Temperature at 0.46 MPa (66 psi)	250 Â°C	482 Â°F	ASTM D1525, HDT Method B
Flammability, UL94	HB @Thickness 1.60 mm	HB @Thickness 0.0630 in	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China