

Lubriplate 110 Calcium Type Multi-Purpose Grease

Category: Fluid, Lubricant, Calcium Gellant

Material Notes:

These water resistant calcium type greases are designed for plain bearings, cams, slides, and other light-duty applications where temperatures do not exceed 170°F. See special applications. Applications: Brake lubricant. Not for disc brakes. 100 & 130 Series Greases are available in Tubes, Cans, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-110-Calcium-Type-Multi-Purpose-Grease.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	300 SUS	300 SUS	
Kinematic Viscosity at 40°C (104°F)	58 cSt	58 cSt	

Mechanical Properties	Metric	English	Comments	
Penetration P(0), 1/10 mm	235	235	Unknown Amount of Work	
Penetration P(60), 1/10 mm	260	260	Unknown Amount of Work	

Thermal Properties	Metric	English	Comments	
Maximum Service Temperature, Air	76.7 °C	170 °F		
Minimum Service Temperature, Air	-23.3 °C	-10.0 °F	Approx. Cold test	
Dropping Point	87.8 °C	190 °F	ASTM Test	

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW	
NLGI Grade	2.5	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China