

Lubriplate 130-A Calcium Type Multi-Purpose Grease

Category : Fluid , Lubricant , Calcium Gellant

Material Notes:

These water resistant calcium type greases are designed for plain bearings, cams, slides, and other light-duty applications where temperatures do not exceed 170°F. See special applications. Applications: Cams, guides, open gears. 100 & 130 Series Greases are available in Tubes, Cans, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-130-A-Calcium-Type-Multi-Purpose-Grease.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	750 SUS	750 SUS	
Kinematic Viscosity at 40°C (104°F)	135 cSt	135 cSt	

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	235	235	Unknown Amount of Work
Penetration P(60), 1/10 mm	260	260	Unknown Amount of Work

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	76.7 °C	170 °F	
Minimum Service Temperature, Air	-6.67 °C	20.0 °F	Approx. Cold test
Dropping Point	93.3 °C	200 °F	ASTM Test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW/EP	
NLGI Grade	2.5	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China