

Lubriplate 176 No. Inorganic/Organic Grease For Open Gearing

Category : Fluid , Lubricant , Lithium Gellant

Material Notes:

This adhesive, semi-fluid grease is used for all types of open gears lubricated by centralized systems. Provides good pumpability without the use of harmful solvents. Applications: Open gears lubricated centralized systems. No. 176 is available in Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-176-No-InorganicOrganic-Grease-For-Open-Gearing.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	1650 SUS	1650 SUS	
Kinematic Viscosity at 40°C (104°F)	313 cSt	313 cSt	

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	400	400	Unknown Amount of Work
Penetration P(60), 1/10 mm	430	430	Unknown Amount of Work

Thermal Properties	Metric	English	Comments
Minimum Service Temperature, Air	-15.0 °C	5.00 °F	Approx. Cold test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW/EP	
NLGI Grade	00	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China