

## Lubriplate 220 SYN High Temp 100% Ester-Based Multi-Purpose Synthetic Fluid

Category: Fluid, Lubricant

## **Material Notes:**

These 100% ester-based synthetic lubricants are recommended for applications that are exposed to high operating temperatures and must maintain a clean lubricated surface. Available in ISO viscosity grades 68 and 220. Proven successful in applications in excess of 600°F/316°C.Applications: Recommended for use on bakery oven chains, drying oven chains, tenter frame chains, heat treating chains, paint curing oven chains and any other type of bearing/slide/gearbox applications where they are exposed to high operating temperatures and must maintain a clean lubricated surface. SYN High Temp 68 & 220 are available in Pails & Drums.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Lubriplate-220-SYN-High-Temp-100-Ester-Based-Multi-Purpose-Synthetic-Fluid.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	92	92	Viscosity Index
	220	220	ISO Grade
Saybolt Viscosity at 100°F	1112 SUS	1112 SUS	
Saybolt Viscosity at 210°F	102 SUS	102 SUS	
Kinematic Viscosity at 40°C (104°F)	220 cSt	220 cSt	
Kinematic Viscosity at 100°C (212°F)	19 cSt	19 cSt	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	>= 316 °C	>= 600 °F	
Pour Point	-20.6 °C	-5.00 °F	
Flammability Test	580	580	[°F] Fire Point
Flash Point	274 °C	525 °F	

Descriptive Properties	Value	Comments
SAE No.	90	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842



Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China