

## Lubriplate 32 Turbine Oil Petroleum-Based Air Compressor Fluid

Category : Fluid , Lubricant

**Material Notes:**

This high-performance, zinc-free fluid meets the requirements of most centrifugal air compressors. Provides excellent oxidation resistance.

Turbine Oil 32 is available in Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-32-Turbine-Oil-Petroleum-Based-Air-Compressor-Fluid.php](http://www.lookpolymers.com/polymer_Lubriplate-32-Turbine-Oil-Petroleum-Based-Air-Compressor-Fluid.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	32	32	ISO Grade
	113	113	Viscosity Index
Saybolt Viscosity at 100Å°F	152 SUS	152 SUS	
Saybolt Viscosity at 210Å°F	44 SUS	44 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	32 cSt	32 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	5.0 cSt	5.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-23.3 Å°C	-10.0 Å°F	
Flammability Test	440	440	[Å°F] Fire Point
Flash Point	199 Å°C	390 Å°F	

Descriptive Properties	Value	Comments
SAE No.	10	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China