

## Lubriplate 68-N Naphthenic Refrigeration Compressor Oil

Category : Fluid , Lubricant , Alkylated Naphthalene (AN)

**Material Notes:**

These highly refined lubricants are formulated for use in refrigeration compressor systems utilizing ammonia, CFC (chlorofluorocarbon) and HCFC (hydrochlorofluorocarbon) refrigerants such as R-717, R-11, R-12, R-13, R-113, R-114, R-115, R-22, R-123, R-141b, R-142b, R-500, R-501 and R-502. They are not recommended for use with HFC (hydrofluorocarbon) refrigerants such as HFC-134a (R-134a).

Refrigeration Compressor Oils 68N & 68P are available in Pails & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-68-N-Naphthenic-Refrigeration-Compressor-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-68-N-Naphthenic-Refrigeration-Compressor-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	28	28	Viscosity Index
	68	68	ISO Grade
Saybolt Viscosity at 100Å°F	330 SUS	330 SUS	
Saybolt Viscosity at 210Å°F	48 SUS	48 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	65 cSt	65 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	7.0 cSt	7.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-37.2 Å°C	-35.0 Å°F	
Flammability Test	435	435	[Å°F] Fire Point
Flash Point	196 Å°C	385 Å°F	

Descriptive Properties	Value	Comments
SAE No.	20	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China