

Lubriplate 68-P Semi-Synthetic Refrigeration Compressor Oil

Category : Fluid , Lubricant

Material Notes:

These highly refined lubricants are formulated for use in refrigeration compressor systems utilizing ammonia, CFC (chlorofluorocarbon) and HCFO (hydrochlorofluorocarbon) refrigerants such as R-717, R-11, R-12, R-13, R-113, R-114, R-115, R-22, R-123, R-141b, R-142b, R-500, R-501 and R-502. They are not recommended for use with HFC (hydrofluorocarbon) refrigerants such as HFC-134a (R-134a).

Refrigeration Compressor Oils 68N & 68P are available in Pails & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-68-P-Semi-Synthetic-Refrigeration-Compressor-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	68	68	ISO Grade
	106	106	Viscosity Index
Saybolt Viscosity at 100Å°F	315 SUS	315 SUS	
Saybolt Viscosity at 210Å°F	42 SUS	42 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	63 cSt	63 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	9.0 cSt	9.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-38.9 Å°C	-38.0 Å°F	
Flammability Test	510	510	[Å°F] Fire Point
Flash Point	242 Å°C	468 Å°F	

Descriptive Properties	Value	Comments
SAE No.	20	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China