

Lubriplate 72-C Oil Food Machinery Oil

Category : Fluid , Lubricant

Material Notes:

Class H-2** oil, for use as a steam peeler oil as it provides an oiliness film which prevents chatter. Available in Bottles, Jugs, Pails, 1/4 Drums and Drums H-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. **H-2 Class lubricants may be used as a lubricant or anti-rust agent on equipment in which there is no possibility of the lubricated part contacting the edible product. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-72-C-Oil-Food-Machinery-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	110	110	Viscosity Index
	150	150	ISO Grade
Saybolt Viscosity at 100Â°F	750 SUS	750 SUS	
Saybolt Viscosity at 210Â°F	75 SUS	75 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	151 cSt	151 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	13 cSt	13 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-9.44 Â°C	15.0 Â°F	
Flammability Test	520	520	[Â°F] Fire Point
Flash Point	254 Â°C	490 Â°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	90	
SAE No.	40	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China