

Lubriplate 730-0 Aluminum Complex Multi-Purpose Grease

Category : Fluid , Lubricant , Aluminum Gellant

Material Notes:

High performance aluminum complex greases that provide high load carrying ability and AW protection with high resistance to water, steam, and other corrosive action. Available in 3 NLGI densities for a wide range of applications and temperatures. No. 730-2 is NLGI GC-LB certified. Applications: Centralized systems adverse conditions. 730 Series Greases are available in Cans, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-730-0-Aluminum-Complex-Multi-Purpose-Grease.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100Â°F	800 SUS	800 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	151 cSt	151 cSt	

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	355	355	Unknown Amount of Work
Penetration P(60), 1/10 mm	385	385	Unknown Amount of Work

Thermal Properties	Metric	English	Comments
Minimum Service Temperature, Air	-23.3 Â°C	-10.0 Â°F	Approx. Cold test
Dropping Point	241 Â°C	465 Â°F	ASTM Test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW/EP	
NLGI Grade	0	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China