

## Lubriplate 930-2 Bentone Type Multi-Purpose Grease

Category : Fluid , Lubricant , Clay Gellant

**Material Notes:**

Formulated for higher temperature applications. They are shear stable, multi-purpose greases for both plain and anti-friction bearings. This series works well up to 375Â°F / 191Â°C and for short intervals up to 400Â°F / 204Â°C. Available in 4 NLGI densities for a wide range of applications. Applications: Multi-purpose, high temperatures.930 Series Greases are available in Cartridges, Tubes, Cans, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-930-2-Bentone-Type-Multi-Purpose-Grease.php](http://www.lookpolymers.com/polymer_Lubriplate-930-2-Bentone-Type-Multi-Purpose-Grease.php)

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100Â°F	750 SUS	750 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	135 cSt	135 cSt	

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	265	265	Unknown Amount of Work
Penetration P(60), 1/10 mm	295	295	Unknown Amount of Work

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	191 Â°C	375 Â°F	
	204 Â°C	400 Â°F	Short Intervals
Minimum Service Temperature, Air	-12.2 Â°C	10.0 Â°F	Approx. Cold test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW/EP	
NLGI Grade	2	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China