

Lubriplate 930-AA Bentone Type Multi-Purpose Grease

Category : Fluid , Lubricant , Clay Gellant

Material Notes:

Formulated for higher temperature applications. They are shear stable, multi-purpose greases for both plain and anti-friction bearings. This series works well up to 375°F / 191°C and for short intervals up to 400°F / 204°C. Available in 4 NLGI densities for a wide range of applications. Applications: High temperatures, automatic dispensers. 930 Series Greases are available in Cartridges, Tubes, Cans, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-930-AA-Bentone-Type-Multi-Purpose-Grease.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	750 SUS	750 SUS	
Kinematic Viscosity at 40°C (104°F)	135 cSt	135 cSt	

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	310	310	Unknown Amount of Work
Penetration P(60), 1/10 mm	340	340	Unknown Amount of Work

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	191 °C	375 °F	
	204 °C	400 °F	Short Intervals
Minimum Service Temperature, Air	-17.8 °C	0.000 °F	Approx. Cold test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW/EP	
NLGI Grade	1	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China