

Lubriplate AC-0 Petroleum-Based Air Compressor Fluid

Category: Fluid, Lubricant

Material Notes:

Formulated to reduce carbon & varnish buildup. They contain fluid zinc to effectively fight friction & wear thus reducing heat & foaming.

Available in six ISO grades.AC Series Air Compressor Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-AC-0-Petroleum-Based-Air-Compressor-Fluid.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	32	32	ISO Grade
	136	136	Viscosity Index
Saybolt Viscosity at 100°F	160 SUS	160 SUS	
Saybolt Viscosity at 210°F	46 SUS	46 SUS	
Kinematic Viscosity at 40°C (104°F)	31 cSt	31 cSt	
Kinematic Viscosity at 100°C (212°F)	6.0 cSt	6.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-34.4 °C	-30.0 °F	
Flammability Test	440	440	[°F] Fire Point
Flash Point	213 °C	415 °F	

Descriptive Properties	Value	Comments
SAE No.	10	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China