

Lubriplate AC-2 Petroleum-Based Air Compressor Fluid

Category : Fluid , Lubricant

Material Notes:

Formulated to reduce carbon & varnish buildup. They contain fluid zinc to effectively fight friction & wear thus reducing heat & foaming. Available in six ISO grades.AC Series Air Compressor Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-AC-2-Petroleum-Based-Air-Compressor-Fluid.php

| Physical Properties | Metric | English | Comments |
|----------------------------------------|---------|---------|-----------------|
| Viscosity Measurement | 68 | 68 | ISO Grade |
| | 106 | 106 | Viscosity Index |
| Saybolt Viscosity at 100Â°F | 309 SUS | 309 SUS | |
| Saybolt Viscosity at 210Â°F | 54 SUS | 54 SUS | |
| Kinematic Viscosity at 40Â°C (104Â°F) | 64 cSt | 64 cSt | |
| Kinematic Viscosity at 100Â°C (212Â°F) | 8.0 cSt | 8.0 cSt | |

| Thermal Properties | Metric | English | Comments |
|--------------------|-----------|-----------|------------------|
| Pour Point | -28.9 Â°C | -20.0 Â°F | |
| Flammability Test | 465 | 465 | [Â°F] Fire Point |
| Flash Point | 221 Â°C | 430 Â°F | |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| SAE No. | 20 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China