

Lubriplate AC-2A Petroleum-Based Air Compressor Fluid

Category : Fluid , Lubricant

Material Notes:

Formulated to reduce carbon & varnish buildup. They contain fluid zinc to effectively fight friction & wear thus reducing heat & foaming. Available in six ISO grades.AC Series Air Compressor Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-AC-2A-Petroleum-Based-Air-Compressor-Fluid.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	100	100	ISO Grade
	104	104	Viscosity Index
Saybolt Viscosity at 100Â°F	518 SUS	518 SUS	
Saybolt Viscosity at 210Â°F	66 SUS	66 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	99 cSt	99 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	12 cSt	12 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-26.1 Â°C	-15.0 Â°F	
Flammability Test	480	480	[Â°F] Fire Point
Flash Point	229 Â°C	445 Â°F	

Descriptive Properties	Value	Comments
SAE No.	30	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China