

Lubriplate AC-3 Petroleum-Based Air Compressor Fluid

Category : Fluid , Lubricant

Material Notes:

Formulated to reduce carbon & varnish buildup. They contain fluid zinc to effectively fight friction & wear thus reducing heat & foaming. Available in six ISO grades.AC Series Air Compressor Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-AC-3-Petroleum-Based-Air-Compressor-Fluid.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	102	102	Viscosity Index
	150	150	ISO Grade
Saybolt Viscosity at 100Â°F	690 SUS	690 SUS	
Saybolt Viscosity at 210Â°F	75 SUS	75 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	135 cSt	135 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	14 cSt	14 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-23.3 Â°C	-10.0 Â°F	
Flammability Test	510	510	[Â°F] Fire Point
Flash Point	238 Â°C	460 Â°F	

Descriptive Properties	Value	Comments
SAE No.	40	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China