

## Lubriplate APG-75 Petroleum-Based Gear, Bearing, & Recirculating Oil

Category : Fluid , Lubricant

**Material Notes:**

These heavy-duty, EP (extreme pressure) type oils were developed to meet gear oil needs of most automotive, truck, heavy equipment, and industrial gear boxes requiring an extreme pressure. Meets military specification MIL-PRF-2105E and MIL-L-21050, as well as API categories GL-3, GL-4, GL-5, and MT-1APG Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-APG-75-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-APG-75-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	32	32	ISO Grade
	113	113	Viscosity Index
Saybolt Viscosity at 100Â°F	152 SUS	152 SUS	
Saybolt Viscosity at 210Â°F	44 SUS	44 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	31 cSt	31 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	6.0 cSt	6.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-48.3 Â°C	-55.0 Â°F	
Flammability Test	365	365	[Â°F] Fire Point
Flash Point	177 Â°C	350 Â°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	75W	
SAE No.	10W	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China