

## Lubriplate APG-80 Petroleum-Based Gear, Bearing, & Recirculating Oil

Category: Fluid, Lubricant

## **Material Notes:**

These heavy-duty, EP (extreme pressure) type oils were developed to meet gear oil needs of most automotive, truck, heavy equipment, and industrial gear boxes requiring an extreme pressure. Meets military specification MIL-PRF-2105E and MIL-L-21050, as well as API categories GL-3, GL-4, GL-5, and MT-1APG Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Lubriplate-APG-80-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	68	68	ISO Grade
	113	113	Viscosity Index
Saybolt Viscosity at 100°F	356 SUS	356 SUS	
Saybolt Viscosity at 210°F	58 SUS	58 SUS	
Kinematic Viscosity at 40°C (104°F)	67 cSt	67 cSt	
Kinematic Viscosity at 100°C (212°F)	9.0 cSt	9.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-37.2 °C	-35.0 °F	
Flammability Test	440	440	[°F] Fire Point
Flash Point	193 °C	380 °F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	80W	
SAE No.	20	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China