

## Lubriplate APG 80W-140 Petroleum-Based Gear, Bearing, & Recirculating Oil

Category : Fluid , Lubricant

**Material Notes:**

These heavy-duty, EP (extreme pressure) type oils were developed to meet gear oil needs of most automotive, truck, heavy equipment, and industrial gear boxes requiring an extreme pressure. Meets military specification MIL-PRF-2105E and MIL-L-21050, as well as API categories GL-3, GL-4, GL-5, and MT-1APG Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-APG-80W-140-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-APG-80W-140-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	120	120	Viscosity Index
	320	320	ISO Grade
Saybolt Viscosity at 100Å°F	1300 SUS	1300 SUS	
Saybolt Viscosity at 210Å°F	125 SUS	125 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	248 cSt	248 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	25 cSt	25 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-31.7 Å°C	-25.0 Å°F	
Flammability Test	410	410	[Å°F] Fire Point
Flash Point	193 Å°C	380 Å°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	80W-140	
SAE No.	60	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China