

Lubriplate AS 148 Oil Food Machinery Oil

Category : Fluid , Lubricant

Material Notes:

An ashless oil for bearings, gears and cams where high temps are encountered. For Manzel lubricators and Angelus Seamers. Class H-2.**Available in Bottles, Jugs, Pails, 1/4 Drums and DrumsH-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product.**H-2 Class lubricants may be used as a lubricant or anti-rust agent on equipment in which there is no possibility of the lubricated part contacting the edible product.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-AS-148-Oil-Food-Machinery-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	97	97	Viscosity Index
	220	220	ISO Grade
Saybolt Viscosity at 100Â°F	1041 SUS	1041 SUS	
Saybolt Viscosity at 210Â°F	91 SUS	91 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	200 cSt	200 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	18 cSt	18 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-12.2 Â°C	10.0 Â°F	
Flammability Test	525	525	[Â°F] Fire Point
Flash Point	243 Â°C	470 Â°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	90	
SAE No.	50	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China