

Lubriplate FB 150 USP Mineral Oil-Based Food Machinery Grade Oil

Category : Fluid , Lubricant

Material Notes:

These clear, tacky, adhesive Class H-1 oils resist heavy water washdown and steam. For helical gearboxes, chains, linkages, cams, and slides and wherever a dripless, adhesive fluid lubricant is desired. Available in Bottles, Jugs, Pails, 1/4 Drums and Drums H-1 Class

Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-FB-150-USP-Mineral-Oil-Based-Food-Machinery-Grade-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	93	93	Viscosity Index
	460	460	ISO Grade
Saybolt Viscosity at 100Å°F	1950 SUS	1950 SUS	
Saybolt Viscosity at 210Å°F	127 SUS	127 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	367 cSt	367 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	25 cSt	25 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-17.8 Å°C	0.000 Å°F	
Flammability Test	455	455	[Å°F] Fire Point
Flash Point	202 Å°C	395 Å°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	140	
SAE No.	70	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China