

Lubriplate FB 150L USP Mineral Oil-Based Food Machinery Grade Oil

Category: Fluid, Lubricant

Material Notes:

These clear, tacky, adhesive Class H-1 oils resist heavy water washdown and steam. For helical gearboxes, chains, linkages, cams, and slides and wherever a dripless, adhesive fluid lubricant is desired. Available in Bottles, Jugs, Pails, 1/4 Drums and DrumsH-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-FB-150L-USP-Mineral-Oil-Based-Food-Machinery-Grade-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	100	100	ISO Grade
	108	108	Viscosity Index
Saybolt Viscosity at 100°F	510 SUS	510 SUS	
Saybolt Viscosity at 210°F	67 SUS	67 SUS	
Kinematic Viscosity at 40°C (104°F)	103 cSt	103 cSt	
Kinematic Viscosity at 100°C (212°F)	12 cSt	12 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-20.6 °C	-5.00 °F	
Flammability Test	450	450	[°F] Fire Point
Flash Point	210 °C	410 °F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	80	
SAE No.	30	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers



Address: United North Road 215, Fengxian District, Shanghai City, China