

Lubriplate FMO 1700 AW USP Mineral Oil-Based Food Machinery Grade Oil

Category: Fluid, Lubricant, White Mineral Oil (WMO)

Material Notes:

For use where a Class H-1 oil is required. Manufactured in nine ISO grades for a variety of applications. Anti-wear fortified. NOTE: FMO-350AW is also available in a red and orange color which helps in leak detection. FMO-1100AW and FMO-2400AW pass 12 stages of the FZG test. The original FMO Series products without the anti wear additive system are still available. FMO Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums.H-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-FMO-1700-AW-USP-Mineral-Oil-Based-Food-Machinery-Grade-Oil.php

| Physical Properties | Metric | English | Comments |
|--|----------|----------|-----------------|
| Viscosity Measurement | 95 | 95 | Viscosity Index |
| | 320 | 320 | ISO Grade |
| Saybolt Viscosity at 100°F | 1730 SUS | 1730 SUS | |
| Saybolt Viscosity at 210°F | 120 SUS | 120 SUS | |
| Kinematic Viscosity at 40°C (104°F) | 324 cSt | 324 cSt | |
| Kinematic Viscosity at 100°C (212°F) | 25 cSt | 25 cSt | |

| Thermal Properties | Metric | English | Comments |
|--------------------|----------|---------|-----------------|
| Pour Point | -15.0 °C | 5.00 °F | |
| Flammability Test | 505 | 505 | [°F] Fire Point |
| Flash Point | 221 °C | 430 °F | |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| SAE Gear Oil No. | 140 | |
| SAE No. | 60 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China