

## Lubriplate FMO 3800 AW USP Mineral Oil-Based Food Machinery Grade Oil

Category : Fluid , Lubricant , White Mineral Oil (WMO)

**Material Notes:**

For use where a Class H-1 oil is required. Manufactured in nine ISO grades for a variety of applications. Anti-wear fortified. NOTE: FMO-350AW is also available in a red and orange color which helps in leak detection. FMO-1100AW and FMO-2400AW pass 12 stages of the FZG test. The original FMO Series products without the anti wear additive system are still available. FMO Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. H-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-FMO-3800-AW-USP-Mineral-Oil-Based-Food-Machinery-Grade-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-FMO-3800-AW-USP-Mineral-Oil-Based-Food-Machinery-Grade-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	96	96	Viscosity Index
	680	680	ISO Grade
Saybolt Viscosity at 100Å°F	3864 SUS	3864 SUS	
Saybolt Viscosity at 210Å°F	198 SUS	198 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	690 cSt	690 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	40 cSt	40 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-9.44 Å°C	15.0 Å°F	
Flammability Test	485	485	[Å°F] Fire Point
Flash Point	216 Å°C	420 Å°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	250	

### Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China