

Lubriplate H0-1 Petroleum-Based Heavy-Duty Hydraulic Oil

Category : Fluid , Lubricant

Material Notes:

Formulated for superior performance, this series contains fluid zinc to effectively reduce ring & vane wear. Excellent anti-rust, anti-corrosion, anti-foam and anti-oxidation properties. High aniline points ensure long seal life with fewer leaks. They can withstand elevated temperatures & high pressures over extended drain intervals. High natural V.I. provides stable viscosities over a wide temperature range. Excellent ISO cleanliness ratings. H0 Series Oils are available in Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-H0-1-Petroleum-Based-Heavy-Duty-Hydraulic-Oil.php

| Physical Properties | Metric | English | Comments |
|--|---------|---------|-----------------|
| Viscosity Measurement | 46 | 46 | ISO Grade |
| | 120 | 120 | Viscosity Index |
| Saybolt Viscosity at 100Â°F | 213 SUS | 213 SUS | |
| Saybolt Viscosity at 210Â°F | 49 SUS | 49 SUS | |
| Kinematic Viscosity at 40Â°C (104Â°F) | 42 cSt | 42 cSt | |
| Kinematic Viscosity at 100Â°C (212Â°F) | 7.0 cSt | 7.0 cSt | |

| Thermal Properties | Metric | English | Comments |
|--------------------|-----------|-----------|------------------|
| Pour Point | -31.7 Â°C | -25.0 Â°F | |
| Flammability Test | 450 | 450 | [Â°F] Fire Point |
| Flash Point | 216 Â°C | 420 Â°F | |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| SAE Gear Oil No. | 75 | |
| SAE No. | 20 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China