

Lubriplate H0-3 Petroleum-Based Heavy-Duty Hydraulic Oil

Category : Fluid , Lubricant

Material Notes:

Formulated for superior performance, this series contains fluid zinc to effectively reduce ring & vane wear. Excellent anti-rust, anti-corrosion, anti-foam and anti-oxidation properties. High aniline points ensure long seal life with fewer leaks. They can withstand elevated temperatures & high pressures over extended drain intervals. High natural V.I. provides stable viscosities over a wide temperature range. Excellent ISO cleanliness ratings. H0 Series Oils are available in Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-H0-3-Petroleum-Based-Heavy-Duty-Hydraulic-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	102	102	Viscosity Index
	150	150	ISO Grade
Saybolt Viscosity at 100Â°F	690 SUS	690 SUS	
Saybolt Viscosity at 210Â°F	75 SUS	75 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	135 cSt	135 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	14 cSt	14 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-23.3 Â°C	-10.0 Â°F	
Flammability Test	510	510	[Â°F] Fire Point
Flash Point	238 Â°C	460 Â°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	85	
SAE No.	40	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China