

## Lubriplate H0-4 Petroleum-Based Heavy-Duty Hydraulic Oil

Category : Fluid , Lubricant

**Material Notes:**

Formulated for superior performance, this series contains fluid zinc to effectively reduce ring & vane wear. Excellent anti-rust, anti-corrosion, anti-foam and anti-oxidation properties. High aniline points ensure long seal life with fewer leaks. They can withstand elevated temperatures & high pressures over extended drain intervals. High natural V.I. provides stable viscosities over a wide temperature range. Excellent ISO cleanliness ratings. H0 Series Oils are available in Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-H0-4-Petroleum-Based-Heavy-Duty-Hydraulic-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-H0-4-Petroleum-Based-Heavy-Duty-Hydraulic-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	101	101	Viscosity Index
	150	150	ISO Grade
Saybolt Viscosity at 100Â°F	840 SUS	840 SUS	
Saybolt Viscosity at 210Â°F	83 SUS	83 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	162 cSt	162 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	16 cSt	16 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-17.8 Â°C	0.000 Â°F	
Flammability Test	525	525	[Â°F] Fire Point
Flash Point	243 Â°C	470 Â°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	90	
SAE No.	40	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China