

Lubriplate Low Pour Petroleum-Based Heavy-Duty Hydraulic Oil

Category : Fluid , Lubricant

Material Notes:

ISO 22 petroleum-based oil for low temperature applications. Low Temp Hydraulic Oils are available in Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-Low-Pour-Petroleum-Based-Heavy-Duty-Hydraulic-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	22	22	ISO Grade
	210	210	Viscosity Index
Saybolt Viscosity at 100Å°F	126 SUS	126 SUS	
Saybolt Viscosity at 210Å°F	46 SUS	46 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	25 cSt	25 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	7.0 cSt	7.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-56.7 Å°C	-70.0 Å°F	
Flammability Test	350	350	[Å°F] Fire Point
Flash Point	157 Å°C	315 Å°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	75W	
SAE No.	5W-20	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.comEmail : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China