

Lubriplate MAG-00 Lithium-Polymer Type Grease For Special Applications / Conditions

Category : Fluid , Lubricant , Lithium Gellant

Material Notes:

These multi-purpose, lithium polymer greases have a wide operating temperature range for a variety of applications from -60°F to 300°F.

Applications: Centralized systems, leaking gearboxes. MAG-00 is available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-MAG-00-Lithium-Polymer-Type-Grease-For-Special-Applications-Conditions.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	120 SUS	120 SUS	
Kinematic Viscosity at 40°C (104°F)	23 cSt	23 cSt	

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	149 °C	300 °F	
Minimum Service Temperature, Air	-51.1 °C	-60.0 °F	Approx. Cold test
Dropping Point	171 °C	340 °F	ASTM Test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW/EP	
NLGI Grade	00	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China