

## Lubriplate NO. 3 NO.3 Petroleum-Based Machine Tool Oil

Category: Fluid, Lubricant

## **Material Notes:**

Compounded to impart a unique load carrying film, exceptional lubricity, and anti-friction properties not found in conventional oils of the same viscosity. Machine Tool Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer\_Lubriplate-NO-3-NO3-Petroleum-Based-Machine-Tool-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	98	98	Viscosity Index
	100	100	ISO Grade
Saybolt Viscosity at 100°F	490 SUS	490 SUS	
Saybolt Viscosity at 210°F	58 SUS	58 SUS	
Kinematic Viscosity at 40°C (104°F)	92 cSt	92 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-31.7 °C	-25.0 °F	
Flammability Test	410	410	[°F] Fire Point
Flash Point	199 °C	390 °F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	80W	
SAE No.	30	

## **Contact Songhan Plastic Technology Co.,Ltd.**

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

.. . . . . .

Address: United North Road 215, Fengxian District, Shanghai City, China