

## Lubriplate NO.2 Petroleum-Based Machine Tool Oil

Category : Fluid , Lubricant

**Material Notes:**

Compounded to impart a unique load carrying film, exceptional lubricity, and anti-friction properties not found in conventional oils of the same viscosity. Machine Tool Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-NO2-Petroleum-Based-Machine-Tool-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-NO2-Petroleum-Based-Machine-Tool-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	46	46	ISO Grade
	96	96	Viscosity Index
Saybolt Viscosity at 100Â°F	228 SUS	228 SUS	
Saybolt Viscosity at 210Â°F	45 SUS	45 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	45 cSt	45 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-34.4 Â°C	-30.0 Â°F	
Flammability Test	385	385	[Â°F] Fire Point
Flash Point	185 Â°C	365 Â°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	75W	
SAE No.	20	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China