

## Lubriplate NO.3V Petroleum-Based Machine Tool Oil

Category : Fluid , Lubricant

### Material Notes:

Compounded to impart a unique load carrying film, exceptional lubricity, and anti-friction properties not found in conventional oils of the same viscosity. Machine Tool Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-NO3V-Petroleum-Based-Machine-Tool-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-NO3V-Petroleum-Based-Machine-Tool-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	68	68	ISO Grade
	98	98	Viscosity Index
Saybolt Viscosity at 100°F	326 SUS	326 SUS	
Saybolt Viscosity at 210°F	48 SUS	48 SUS	
Kinematic Viscosity at 40°C (104°F)	62 cSt	62 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-31.7 °C	-25.0 °F	
Flammability Test	395	395	[°F] Fire Point
Flash Point	193 °C	380 °F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	80W	
SAE No.	20	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China