

## Lubriplate NO.8 Petroleum-Based Machine Tool Oil

Category : Fluid , Lubricant

**Material Notes:**

Compounded to impart a unique load carrying film, exceptional lubricity, and anti-friction properties not found in conventional oils of the same viscosity. Machine Tool Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-NO8-Petroleum-Based-Machine-Tool-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-NO8-Petroleum-Based-Machine-Tool-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	90	90	Viscosity Index
	460	460	ISO Grade
Saybolt Viscosity at 100Å°F	2300 SUS	2300 SUS	
Saybolt Viscosity at 210Å°F	142 SUS	142 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	432 cSt	432 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	28 cSt	28 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-17.8 Å°C	0.000 Å°F	
Flammability Test	515	515	[Å°F] Fire Point
Flash Point	224 Å°C	435 Å°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	140	
SAE No.	70	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China