

## Lubriplate PURE TAC PURE Aluminum Complex USP Mineral Oil-Based Food Machinery Grade Grease

Category : Fluid , Lubricant , Aluminum Gellant

### Material Notes:

This tacky, adhesive, highly water resistant, Class H-1 grease is designed for applications subjected to chemically treated water, heat and steam. For all types of medium to slow speed bearings, open gears and hydrostatic cooker chains. PURE TAC is available in Cartridges, Pails, 1/4 Drums and Drums. H-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-PURE-TAC-PURE-Aluminum-Complex-USP-Mineral-Oil-Based-Food-Machinery-Grade-Grease.php](http://www.lookpolymers.com/polymer_Lubriplate-PURE-TAC-PURE-Aluminum-Complex-USP-Mineral-Oil-Based-Food-Machinery-Grade-Grease.php)

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100Å°F	6500 SUS	6500 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	1187 cSt	1187 cSt	

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	265	265	Unknown Amount of Work
Penetration P(60), 1/10 mm	295	295	Unknown Amount of Work

Thermal Properties	Metric	English	Comments
Minimum Service Temperature, Air	-3.89 Å°C	25.0 Å°F	Approx. Cold test
Dropping Point	271 Å°C	520 Å°F	ASTM Test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW	
NLGI Grade	2	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China