

## Lubriplate SPO-222 Petroleum-Based Gear, Bearing, & Recirculating Oil

Category : Fluid , Lubricant

### Material Notes:

Petroleum-based oils specifically designed for industrial applications such as gear cases, bearings, chains, machine ways, and general oiling. These tacky lubricants will provide anti-wear lubrication for high sliding action in worm gears. They are also excellent for bevel, helical, and spur gears. They can be used with silver alloy, copper, and copper alloy bearings. Excellent for use in high moisture and high temperature applications. Provides performance comparable to synthetic lubricants. SPO Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-SPO-222-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-SPO-222-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	68	68	ISO Grade
	109	109	Viscosity Index
Saybolt Viscosity at 100Â°F	317 SUS	317 SUS	
Saybolt Viscosity at 210Â°F	55 SUS	55 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	63 cSt	63 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	9.0 cSt	9.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-34.4 Â°C	-30.0 Â°F	
Flammability Test	465	465	[Â°F] Fire Point
Flash Point	213 Â°C	415 Â°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	80W	
SAE No.	20W	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China