

Lubriplate SPO-244 Petroleum-Based Gear, Bearing, & Recirculating Oil

Category : Fluid , Lubricant

Material Notes:

Petroleum-based oils specifically designed for industrial applications such as gear cases, bearings, chains, machine ways, and general oiling. These tacky lubricants will provide anti-wear lubrication for high sliding action in worm gears. They are also excellent for bevel, helical, and spur gears. They can be used with silver alloy, copper, and copper alloy bearings. Excellent for use in high moisture and high temperature applications. Provides performance comparable to synthetic lubricants. SPO Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-SPO-244-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	102	102	Viscosity Index
	150	150	ISO Grade
Saybolt Viscosity at 100Â°F	685 SUS	685 SUS	
Saybolt Viscosity at 210Â°F	75 SUS	75 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	135 cSt	135 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	14 cSt	14 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-31.7 Â°C	-25.0 Â°F	
Flammability Test	525	525	[Â°F] Fire Point
Flash Point	238 Â°C	460 Â°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	90	
SAE No.	40	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China