

Lubriplate SPO-277 Petroleum-Based Gear, Bearing, & Recirculating Oil

Category : Fluid , Lubricant

Material Notes:

Petroleum-based oils specifically designed for industrial applications such as gear cases, bearings, chains, machine ways, and general oiling. These tacky lubricants will provide anti-wear lubrication for high sliding action in worm gears. They are also excellent for bevel, helical, and spur gears. They can be used with silver alloy, copper, and copper alloy bearings. Excellent for use in high moisture and high temperature applications. Provides performance comparable to synthetic lubricants. SPO Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-SPO-277-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php

| Physical Properties | Metric | English | Comments |
|--|----------|----------|-----------------|
| Viscosity Measurement | 101 | 101 | Viscosity Index |
| | 460 | 460 | ISO Grade |
| Saybolt Viscosity at 100Â°F | 2260 SUS | 2260 SUS | |
| Saybolt Viscosity at 210Â°F | 148 SUS | 148 SUS | |
| Kinematic Viscosity at 40Â°C (104Â°F) | 432 cSt | 432 cSt | |
| Kinematic Viscosity at 100Â°C (212Â°F) | 30 cSt | 30 cSt | |

| Thermal Properties | Metric | English | Comments |
|--------------------|-----------|----------|------------------|
| Pour Point | -9.44 Â°C | 15.0 Â°F | |
| Flammability Test | 580 | 580 | [Â°F] Fire Point |
| Flash Point | 246 Â°C | 475 Â°F | |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| SAE Gear Oil No. | 140 | |
| SAE No. | 70 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China