

## Lubriplate SPO-299 Petroleum-Based Gear, Bearing, & Recirculating Oil

Category : Fluid , Lubricant

**Material Notes:**

Petroleum-based oils specifically designed for industrial applications such as gear cases, bearings, chains, machine ways, and general oiling. These tacky lubricants will provide anti-wear lubrication for high sliding action in worm gears. They are also excellent for bevel, helical, and spur gears. They can be used with silver alloy, copper, and copper alloy bearings. Excellent for use in high moisture and high temperature applications. Provides performance comparable to synthetic lubricants. SPO Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-SPO-299-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php](http://www.lookpolymers.com/polymer_Lubriplate-SPO-299-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	99	99	Viscosity Index
	1000	1000	ISO Grade
Saybolt Viscosity at 100Å°F	5100 SUS	5100 SUS	
Saybolt Viscosity at 210Å°F	245 SUS	245 SUS	
Kinematic Viscosity at 40Å°C (104Å°F)	950 cSt	950 cSt	
Kinematic Viscosity at 100Å°C (212Å°F)	50 cSt	50 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-12.2 Å°C	10.0 Å°F	
Flammability Test	505	505	[Å°F] Fire Point
Flash Point	232 Å°C	450 Å°F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	250	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China