

Lubriplate SPO-MG Petroleum-Based Gear, Bearing, & Recirculating Oil

Category: Fluid, Lubricant

Material Notes:

Petroleum-based oils specifically designed for industrial applications such as gear cases, bearings, chains, machine ways, and general oiling. These tacky lubricants will provide anti-wear lubrication for high sliding action in worm gears. They are also excellent for bevel, helical, and spur gears. They can be used with silver alloy copper, and copper alloy bearings. Excellent for use in high moisture and high temperature applications. SPO-MG is a semi-synthetic lubricant formulated with a unique blend of synthetic hydrocarbon and mineral base stocks. SPO Series Oils are available in Bottles, Jugs, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-SPO-MG-Petroleum-Based-Gear-Bearing-Recirculating-Oil.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	120	120	Viscosity Index
	220	220	ISO Grade
Saybolt Viscosity at 100°F	1223 SUS	1223 SUS	
Saybolt Viscosity at 210°F	123 SUS	123 SUS	
Kinematic Viscosity at 40°C (104°F)	237 cSt	237 cSt	
Kinematic Viscosity at 100°C (212°F)	25 cSt	25 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-31.7 °C	-25.0 °F	
Flammability Test	465	465	[°F] Fire Point
Flash Point	218 °C	425 °F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	80W-140	
SAE No.	60	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058



Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China