

Lubriplate STO 4 Oil Food Machinery Oil

Category: Fluid, Lubricant

Material Notes:

Special, non-corrosive oil for lubricating stirrups on bottle filling machines. Class H-2.**Available in Bottles, Jugs, Pails, 1/4 Drums and DrumsH-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product.**H-2 Class lubricants may be used as a lubricant or anti-rust agent on equipment in which there is no possibility of the lubricated part contacting the edible product.Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-STO-4-Oil-Food-Machinery-Oil.php

| Physical Properties | Metric | English | Comments |
|-------------------------------------|---------|---------|-----------------|
| Viscosity Measurement | 46 | 46 | ISO Grade |
| | 70 | 70 | Viscosity Index |
| Saybolt Viscosity at 100°F | 255 SUS | 255 SUS | |
| Saybolt Viscosity at 210°F | 47 SUS | 47 SUS | |
| Kinematic Viscosity at 40°C (104°F) | 45 cSt | 45 cSt | |

| Thermal Properties | Metric | English | Comments |
|--------------------|----------|----------|-----------------|
| Pour Point | -34.4 °C | -30.0 °F | |
| Flammability Test | 370 | 370 | [°F] Fire Point |
| Flash Point | 160 °C | 320 °F | |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| SAE Gear Oil No. | 75 | |
| SAE No. | 20 | |

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China