

Lubriplate STO FG Oil USP Mineral -Based Food Machinery Grade

Category : Fluid , Lubricant

Material Notes:

Special, non-corrosive oil for lubricating stirrups on bottle filling machines. Class H-1. Available in Bottles, Jugs, Pails, 1/4 Drums and Drums. H-1 Class Lubricants are manufactured with ingredients that comply with FDA regulation 21 CFR 178.3570 for lubricants with incidental contact with the edible product. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-STO-FG-Oil-USP-Mineral-Based-Food-Machinery-Grade.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	68	68	ISO Grade
	105	105	Viscosity Index
Saybolt Viscosity at 100°F	340 SUS	340 SUS	
Saybolt Viscosity at 210°F	70 SUS	70 SUS	
Kinematic Viscosity at 40°C (104°F)	67 cSt	67 cSt	
Kinematic Viscosity at 100°C (212°F)	13 cSt	13 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-26.1 °C	-15.0 °F	
Flammability Test	485	485	[°F] Fire Point
Flash Point	218 °C	425 °F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	80	
SAE No.	20	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China