

Lubriplate SYN LUBE 22 PAO-Based Multi-Purpose Synthetic Fluid

Category : Fluid , Lubricant , Polyalphaolefin (PAO)

Material Notes:

PAO-based zinc free fluids formulated with state of the art additives to provide outstanding performance over extended drain intervals. Applications: Syn-Lube 22, 32, 46, 68 & 100 are recommended for many types of rotary screw and piston type air compressors, hydraulic systems, blowers, and turbine oil applications. Available in Pails and Drums Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-SYN-LUBE-22-PAO-Based-Multi-Purpose-Synthetic-Fluid.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	22	22	ISO Grade
	138	138	Viscosity Index
Saybolt Viscosity at 100Â°F	129 SUS	129 SUS	
Saybolt Viscosity at 210Â°F	44 SUS	44 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	23 cSt	23 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	5.0 cSt	5.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-56.7 Â°C	-70.0 Â°F	
Flammability Test	470	470	[Â°F] Fire Point
	>= 700	>= 700	[Â°F] Auto-Ignition
Flash Point	216 Â°C	420 Â°F	

Descriptive Properties	Value	Comments
SAE No.	5W	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China