

Lubriplate SYN LUBE 220 PAO-Based Multi-Purpose Synthetic Fluid

Category: Fluid, Lubricant, Polyalphaolefin (PAO)

Material Notes:

PAO-based zinc free fluids formulated with state of the art additives to provide outstanding performance over extended drain intervals. Applications: Syn-Lube 150, 220, 320, 460 & 680 are recommended for many types of rotary screw and piston type air compressors, hydraulic systems, blowers, and turbine oil applications. Available in Jugs, Pails, 1/4 Drums and DrumsInformation provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-SYN-LUBE-220-PAO-Based-Multi-Purpose-Synthetic-Fluid.php

Physical Properties	Metric	English	Comments
Viscosity Measurement	154	154	Viscosity Index
	220	220	ISO Grade
Saybolt Viscosity at 100°F	988 SUS	988 SUS	
Kinematic Viscosity at 40°C (104°F)	199 cSt	199 cSt	
Kinematic Viscosity at 100°C (212°F)	25 cSt	25 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-48.3 °C	-55.0 °F	
Flammability Test	580	580	[°F] Fire Point
Flash Point	282 °C	540 °F	

Descriptive Properties	Value	Comments
SAE Gear Oil No.	90	
SAE No.	50	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058 Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China