

## Lubriplate SYN LUBE 32 PAO-Based Multi-Purpose Synthetic Fluid

Category : Fluid , Lubricant , Polyalphaolefin (PAO)

**Material Notes:**

PAO-based zinc free fluids formulated with state of the art additives to provide outstanding performance over extended drain intervals. Applications: Syn-Lube 22, 32, 46, 68 & 100 are recommended for many types of rotary screw and piston type air compressors, hydraulic systems, blowers, and turbine oil applications. Available in Pails and Drums Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-SYN-LUBE-32-PAO-Based-Multi-Purpose-Synthetic-Fluid.php](http://www.lookpolymers.com/polymer_Lubriplate-SYN-LUBE-32-PAO-Based-Multi-Purpose-Synthetic-Fluid.php)

Physical Properties	Metric	English	Comments
Viscosity Measurement	32	32	ISO Grade
	136	136	Viscosity Index
Saybolt Viscosity at 100Â°F	160 SUS	160 SUS	
Saybolt Viscosity at 210Â°F	47 SUS	47 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	32 cSt	32 cSt	
Kinematic Viscosity at 100Â°C (212Â°F)	6.0 cSt	6.0 cSt	

Thermal Properties	Metric	English	Comments
Pour Point	-56.7 Â°C	-70.0 Â°F	
Flammability Test	505	505	[Â°F] Fire Point
	>= 700	>= 700	[Â°F] Auto-Ignition
Flash Point	243 Â°C	470 Â°F	

Descriptive Properties	Value	Comments
SAE No.	10	

## Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China