

## Lubriplate SYN LUBE 68 PAO-Based Multi-Purpose Synthetic Fluid

Category : Fluid , Lubricant , Polyalphaolefin (PAO)

**Material Notes:**

PAO-based zinc free fluids formulated with state of the art additives to provide outstanding performance over extended drain intervals. Applications: Syn-Lube 22, 32, 46, 68 & 100 are recommended for many types of rotary screw and piston type air compressors, hydraulic systems, blowers, and turbine oil applications. Available in Pails and Drums Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-SYN-LUBE-68-PAO-Based-Multi-Purpose-Synthetic-Fluid.php](http://www.lookpolymers.com/polymer_Lubriplate-SYN-LUBE-68-PAO-Based-Multi-Purpose-Synthetic-Fluid.php)

| Physical Properties                    | Metric  | English | Comments        |
|--|---------|---------|-----------------|
| Viscosity Measurement                  | 68      | 68      | ISO Grade       |
|  | 138     | 138     | Viscosity Index |
| Saybolt Viscosity at 100Â°F            | 314 SUS | 314 SUS |                 |
| Saybolt Viscosity at 210Â°F            | 58 SUS  | 58 SUS  |                 |
| Kinematic Viscosity at 40Â°C (104Â°F)  | 66 cSt  | 66 cSt  |                 |
| Kinematic Viscosity at 100Â°C (212Â°F) | 10 cSt  | 10 cSt  |                 |

| Thermal Properties | Metric    | English   | Comments            |
|--------------------|-----------|-----------|---------------------|
| Pour Point         | -51.1 Â°C | -60.0 Â°F |                     |
| Flammability Test  | 580       | 580       | [Â°F] Fire Point    |
|                    | >= 700    | >= 700    | [Â°F] Auto-Ignition |
| Flash Point        | 268 Â°C   | 515 Â°F   |                     |

| Descriptive Properties | Value | Comments |
|------------------------|-------|----------|
| SAE Gear Oil No.       | 80W   |          |
| SAE No.                | 20    |          |

### Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China