

Lubriplate TEMP HIGH Bentone Type Multi-Purpose Grease For Special Conditions

Category : Fluid , Lubricant , Clay Gellant

Material Notes:

Multi-purpose, high temperature, bentone type grease workable from 40Â°F to 500Â°F. Applications: Multi-Purpose, high temp. applications HIGH TEMP is available in Cartridges, Cans, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-TEMP-HIGH-Bentone-Type-Multi-Purpose-Grease-For-Special-Conditions.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100Â°F	2600 SUS	2600 SUS	
Kinematic Viscosity at 40Â°C (104Â°F)	497 cSt	497 cSt	

Mechanical Properties	Metric	English	Comments
Penetration P(0), 1/10 mm	265	265	Unknown Amount of Work
Penetration P(60), 1/10 mm	295	295	Unknown Amount of Work

Thermal Properties	Metric	English	Comments
Maximum Service Temperature, Air	260 Â°C	500 Â°F	
Minimum Service Temperature, Air	-12.2 Â°C	10.0 Â°F	Approx. Cold test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW	
NLGI Grade	2	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com

Email : sales@lookpolymers.com

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215,Fengxian District, Shanghai City,China