Lubriplate TEMP LOW Anhydrous Calcium Multi-Purpose Grease For Special Conditions

Category : Fluid , Lubricant , Calcium Gellant

Material Notes:

Multi-purpose, anhydrous calcium based grease for cold temperature applications down to -60°F. Applications: Cold temps., multi-

purpose, fifth wheels. LOW TEMP is available in Cartridges, Tubes, Cans, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-TEMP-LOW-Anhydrous-Calcium-Multi-Purpose-Grease-For-Special-Conditions.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	90 SUS	90 SUS	
Kinematic Viscosity at 40°C (104°F)	16 cSt	16 cSt	

Mechanical Properties	Metric	English	Comments	
Penetration P(0), 1/10 mm	290	290	Unknown Amount of Work	
Penetration P(60), 1/10 mm	320	320	Unknown Amount of Work	

Thermal Properties	Metric	English	Comments	
Minimum Service Temperature, Air	-51.1 °C	-60.0 °F	Approx. Cold test	
Dropping Point	138 °C	280 °F	ASTM Test	

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW	
NLGI Grade	1.5	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website : www.lookpolymers.com Email : sales@lookpolymers.com Tel : +86 021-51131842 Mobile : +86 13061808058 Skype : lookpolymers Address : United North Road 215,Fengxian District, Shanghai City,China