

## Lubriplate Temp G.S. Low Lithium Based Grease For Open Gearing

Category : Fluid , Lubricant , Lithium Gellant

### Material Notes:

Lithium-based open gear grease made for all types of open gears. Available in 4 formulas for a variety of conditions and temperatures.

Applications: Open gears, slides, fifth wheels, low temps. Gear Shield Series Greases are available in Cans, Pails, 1/4 Drums &

Drums. Information provided by Lubriplate

Order this product through the following link:

[http://www.lookpolymers.com/polymer\\_Lubriplate-Temp-GS-Low-Lithium-Based-Grease-For-Open-Gearing.php](http://www.lookpolymers.com/polymer_Lubriplate-Temp-GS-Low-Lithium-Based-Grease-For-Open-Gearing.php)

| Physical Properties                 | Metric  | English | Comments |
|-------------------------------------|---------|---------|----------|
| Saybolt Viscosity at 100°F          | 300 SUS | 300 SUS |          |
| Kinematic Viscosity at 40°C (104°F) | 58 cSt  | 58 cSt  |          |

| Mechanical Properties      | Metric | English | Comments               |
|----------------------------|--------|---------|------------------------|
| Penetration P(0), 1/10 mm  | 265    | 265     | Unknown Amount of Work |
| Penetration P(60), 1/10 mm | 295    | 295     | Unknown Amount of Work |

| Thermal Properties               | Metric   | English  | Comments          |
|----------------------------------|----------|----------|-------------------|
| Minimum Service Temperature, Air | -28.9 °C | -20.0 °F | Approx. Cold test |
| Dropping Point                   | 204 °C   | 400 °F   | ASTM Test         |

| Descriptive Properties               | Value | Comments |
|--------------------------------------|-------|----------|
| Antiwear (AW)/ Extreme Pressure (EP) | AW    |          |
| NLGI Grade                           | 2     |          |
| Rust/Oxidative Additives             | YES   |          |
| Water Resistant                      | YES   |          |

## Contact Songhan Plastic Technology Co.,Ltd.

Website : [www.lookpolymers.com](http://www.lookpolymers.com)

Email : [sales@lookpolymers.com](mailto:sales@lookpolymers.com)

Tel : +86 021-51131842

Mobile : +86 13061808058

Skype : lookpolymers

Address : United North Road 215, Fengxian District, Shanghai City, China