

Lubriplate X-Heavy G.S. Lithium Based Grease For Open Gearing

Category: Fluid, Lubricant, Lithium Gellant

Material Notes:

Lithium-based open gear grease made for all types of open gears. Available in 4 formulas for a variety of conditions and temperatures. Gear Shield Extra Heavy is for adverse conditions. Applications: Open gears, adverse conditions. Excellent for fifth wheel applications. Gear Shield X-Heavy is available in Aerosol, Caulk Type Cartridges, Cans, Pails, 1/4 Drums & Drums. Information provided by Lubriplate

Order this product through the following link:

http://www.lookpolymers.com/polymer_Lubriplate-X-Heavy-GS-Lithium-Based-Grease-For-Open-Gearing.php

Physical Properties	Metric	English	Comments
Saybolt Viscosity at 100°F	2000 SUS	2000 SUS	
Kinematic Viscosity at 40°C (104°F)	432 cSt	432 cSt	

Mechanical Properties	Metric	English	Comments	
Penetration P(0), 1/10 mm	235	235	Unknown Amount of Work	
Penetration P(60), 1/10 mm	260	260	Unknown Amount of Work	

Thermal Properties	Metric	English	Comments
Minimum Service Temperature, Air	-6.67 °C	20.0 °F	Approx. Cold test
Dropping Point	188 °C	370 °F	ASTM Test

Descriptive Properties	Value	Comments
Antiwear (AW)/ Extreme Pressure (EP)	AW	
NLGI Grade	2.5	
Rust/Oxidative Additives	YES	
Water Resistant	YES	

Contact Songhan Plastic Technology Co.,Ltd.

Website: www.lookpolymers.com Email: sales@lookpolymers.com

Tel: +86 021-51131842 Mobile: +86 13061808058

Skype: lookpolymers

Address: United North Road 215, Fengxian District, Shanghai City, China